

## § 411.36

standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations
TSS .....	Not to exceed 50 mg/l.
pH .....	Within the range 6.0 to 9.0.

(b) Any overflow from facilities designed, constructed and operated to treat to the applicable limitations the precipitation and runoff resulting from a 10-year, 24-hour precipitation event shall not be subject to the limitations of this section.

[42 FR 10681, Feb. 23, 1977]

## § 411.36 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33951, June 29, 1995]

## § 411.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology.

(a) Subject to the provisions of paragraph (b) of this section, the following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology.

Effluent characteristic	Effluent limitations
TSS .....	Not to exceed 50 mg/l.
pH .....	Within the range 6.0 to 9.0.

(b) Any untreated overflow from facilities designed, constructed and oper-

## 40 CFR Ch. I (7–1–06 Edition)

ated to treat the volume of runoff from materials storage piles which results from a 10-year, 24-hour rainfall event shall not be subject to the pH and TSS limitations stipulated in paragraph (a) of this section.

[39 FR 6591, Feb. 20, 1974. Redesignated and amended at 44 FR 50741, Aug. 29, 1979]

## PART 412—CONCENTRATED ANIMAL FEEDING OPERATIONS (CAFO) POINT SOURCE CATEGORY

Sec.

- 412.1 General applicability.
- 412.2 General definitions.
- 412.3 General pretreatment standards.
- 412.4 Best management practices (BMPs) for land application of manure, litter, and process wastewater.

### Subpart A—Horses and Sheep

- 412.10 Applicability.
- 412.11 [Reserved]
- 412.12 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).
- 412.13 Effluent limitations attainable by the application of the best available technology economically achievable (BAT).
- 412.14 [Reserved]
- 412.15 New source performance standards (NSPS).

### Subpart B—Ducks

- 412.20 Applicability.
- 412.21 Special definitions.
- 412.22 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).
- 412.23–412.24 [Reserved]
- 412.25 New source performance standards (NSPS).
- 412.26 Pretreatment standards for new sources (PSNS).

### Subpart C—Dairy Cows and Cattle Other Than Veal Calves

- 412.30 Applicability.
- 412.31 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).
- 412.32 Effluent limitations attainable by the application of the best conventional pollutant control technology (BCT).
- 412.33 Effluent limitations attainable by the application of the best available technology economically achievable (BAT).